

<b>Technology</b>	<b>C400 (Standard)</b>	<b>C400 (toe-plate version)</b>
<b>Measurements</b>	Height = min. <b>1512 mm</b> max. <b>1812 mm</b> Width = <b>564 mm</b> Depth = <b>782 mm</b>	Height = min. <b>1512 mm</b> max. <b>1812 mm</b> Width = <b>564 mm</b> Depth = <b>500 mm</b>
<b>Weight</b>	CargoMaster = <b>79.9 kg</b> Charger = <b>0.3 kg</b> Battery pack = <b>4.1 kg</b> Total weight = <b>84.3 kg</b>	CargoMaster = <b>77.0 kg</b> Charger = <b>0.3 kg</b> Battery pack = <b>4.1 kg</b> Total weight = <b>81.4 kg</b>
<b>Lifting capacity</b>	400kg	
<b>Climbing speed</b>	3-8 steps / minute	
<b>Range with one charge of the batteries</b>	8-15 levels(equates 120-225 steps)	
<b>Max. lifting toe plate</b>	700mm	
<b>Max. lowering toe plate</b>	210 mm	
<b>Max. height of step</b>	210mm	
<b>Min. depth of the step's surface</b>	140mm	
<b>Necessary step width (straight stairs)</b>	Maneuvering space 100 mm (CargoMaster + Load)	
<b>Min. platform size</b>	Depends on the attendant 's height and the height of the load	
<b>Batteries</b>	2 x 12 V / 5 Ah (sealed lead acid)	
<b>Direct current motor - drive</b>	24 V / 275 W	
<b>Noise level</b>	The device 's A weighted noise level lies typically below 70 dB	
<b>Storing/operating temperature: device</b>	0° C up to +60° C / -30° C up to +50°C	
<b>Storing/operating temperature: device</b>	0° C up to +60° C / -30° C up to +50°C	